



HAYNES[®] PRODUCT INFORMATION

THE WORLD'S LEADING MANUFACTURER OF PREMIUM FOOD GRADE LUBRICANTS



LUBRI-FILM PLUS

Extended Wear Lubricating Grease

Packaged in tubes (7g, 1oz, & 4oz), pails, and drums.

NSF Rated H-1

NLGI: 1
COLOR: None
ODOR: None
TEXTURE: Smooth

Haynes Lubri-Film Plus is a heavy duty sanitary lubricant with extended performance, low friction properties. This lubricant is authorized by the NSF rated H1 for use in food processing plants for incidental food contact. All ingredients are FDA approved.

Haynes Lubri-Film Plus is designed for longer lubrication intervals, eliminating downtime to relubricate the equipment. This lubricant wears evenly on all moving parts, preventing metal to metal contact and equipment damage. The Haynes Lubri-Film Plus will not dry or gum on the equipment and is highly resistant to separation or bleed. It is a time saver because it cleans off of the equipment easily.

Haynes[®] Lubri-Film Plus is packaged in two sizes; 1oz tube and 4oz tube.

COMMON APPLICATIONS:

- ◆ Pumps
- ◆ Meat Slicing Equipment
- ◆ Cheese Processing Equipment
- ◆ Dispensing Units
- ◆ Bearings
- ◆ Packings
- ◆ Plug Valves
- ◆ Centralized Lubrication Equipment
- ◆ Mixers
- ◆ Slicers
- ◆ Batch Freezers
- ◆ Soft-Serve Machines
- ◆ Shake Machines
- ◆ Frozen Drink Machines
- ◆ Cappuccino Machines
- ◆ Yogurt Machines
- ◆ Pasta Machines
- ◆ Dispensing Units
- ◆ Hospital Beds
- ◆ Beverage Equipment

TECHNICAL DATA INFORMATION

<i>TEST</i>	<i>ASTM Method</i>	<i>Typical Test Results</i>
Low Temperature Torque (Start 1 Hour)	1478	266.177
Viscosity (Saybolt @ 210°F)	D 445	350
Four Ball Wear Scar Diameter, mm	D2266	0.49
Co-Efficient of Friction	SRV	0.0892
Water Spray Off, % off Loss	D4049	94.00
Water Washout @ 100°F, % Loss	D1264	29.5
Operating Range, Min °F, Max °F		-15° - 210°F